



**CUTLITE PENTA**

DEVELOPMENT  
OF HIGH-TECH LASER  
**METAL-CUTTING**  
**MACHINES**

INDUSTRIAL DIVISION OF

**ELEN**  
GROUP

# Contents

<b>The Company</b>	<b>6</b>
<b>2D Cutting Systems</b>	<b>12</b>
PLUS	<b>14</b>
LME	<b>22</b>
<b>Software 2D</b>	<b>28</b>
Smart manager 6	<b>30</b>
Smart composer	<b>31</b>
<b>Automation</b>	<b>32</b>
Loading/unloading systems and warehouses	<b>34</b>
<b>Laser Sources</b>	<b>38</b>
<b>Hardware Solutions</b>	<b>40</b>



*Iron sample 35 mm*

# THE COMPANY


Cutlite Penta was founded in 1992 as a division of the El.En. group, and began construction of the first machines to cut wood and plastic materials using resources that were **designed and constructed at El.En.** The group grew steadily over the years, expanding both in the industrial and medical sectors. El.En. Group is a well-established Italian company, listed on both the Italian and US stock exchanges, with a market capitalisation of almost €1.34 billion. Cutlite Penta forms part of the industrial division of the El.En. Group, and has manufacturing and sales facilities around the world: Italy, France, China, and Brazil.

**To date, it employs over 850 people as direct employees of the industrial group, includes over 5,500 laser machines equipped with fiber laser sources installed worldwide, and over 80,000 m<sup>2</sup> of manufacturing space.**

Long-running, well developed experience combined with a profound knowledge of the dynamics of metal cutting have allowed us to become a standard for our customers. The industrial group, which had a total turnover of €63 million in 2016, has been growing at a dynamic pace, reaching a turnover of €150 million by the end of 2020. **In December 2021, the industrial group closed the year with a total turnover of €240,000,000.**

Despite the difficulties caused by the international emergency, the group's growth has been steady and exponential. In 2021, the turnover in the first six months of operation already exceeded the previous year's figure. With hard work and dedication, Cutlite Penta is consolidating its position as a global player in metal laser cutting, developing, designing and manufacturing each and every part of the cutting systems in-house.

## INDUSTRIAL GROUP TURNOVER



## MISSION

Cutlite Penta's objective has always been to create systems that guarantee high levels of productivity and quality with low running costs, enabling its customers to be extraordinarily competitive.

Cutlite Penta's **R&D department**, which is continually developing its cutting head, proprietary CNC and front-end software, ensures that Cutlite Penta systems are always state-of-the-art.

Flexibility, speed, simplicity of use and ease of familiarisation, are the distinctive features of this new family of systems that will place our customers in a position of being market leaders.


# OUR FIGURES

**850**  
employees

**80.000 m<sup>2</sup>**  
manufacturing areas



# YEARS OF EXPERIENCE AND KNOW-HOW AT YOUR DISPOSAL



Based on El.En. Group's decades of experience with CO<sub>2</sub> laser sources, we have transferred and perfected this advanced, multi-disciplinary know-how from the field of CO<sub>2</sub> laser technology to the field of **FIBER LASER TECHNOLOGY**.

*By partnering with the world's largest manufacturer of laser sources, IPG Photonics, we have access to the best fiber laser sources to develop fast, high-power machines.*

THE FIRST IN EUROPE TO INSTALL HIGH-POWER  
**LASER SOURCES ON CUTTING MACHINES**



# MULTIDISCIPLINARY TECHNOLOGY ON ALL OUR MODELS

## **FLY CUT**

Proprietary on-the-fly cutting technology

## **FLY PIERCING**

Piercing of moving material

## **LINEAR MOTORS**

We only use linear motors in all the systems we manufacture

## **ABSOLUTE ENCODERS**

Guaranteed axis positioning with no need for machine zeroing

## **CUTTING HEAD**

In-house designed and manufactured for all models, enabling high-power handling and significant savings in terms of gas (-20%)

## **SMART MANAGER 6**

Software machine management is identical on all models


## **SMART COMPOSER**

Integrated CAD/CAM on all installed systems

## **RASTER MODULE**

Software and hardware module for image reproduction on sheet metal





## EVO 3 HEAD FOR PLUS AND LME

The Evo 3 cutting head is equipped with a **capacitive sensor**. FIBER PLUS and LME systems use the **Evo 3 autofocus cutting head**, which was designed exclusively by our R&D department and manufactured using Cutlite Penta high-precision mechanical engineering, and is equipped with a contact-free capacitive sensor. The head itself and the focusing lenses can be used with up to **40 kW** laser power and a pressure of 25 bar. A variety of focal configurations are available. The assist gas is **automatically selected** from the 3 different connectible gases - air, nitrogen and oxygen - whose assist pressures are determined automatically on the basis of cutting parameters and materials. The head has a removable cartridge to facilitate replacement of the protective glass.

### CAPACITIVE HEAD

- Integrated contact-free capacitive sensor
- High-pressure gas management
- Cartridge to change focal length
- Connections located entirely at the top
- Contact and impact error management
- Focal lengths of 150 mm - 300 mm
- Maximum pressures 25 bar
- Protective glass



**PERFORMANCE  
ACHIEVABLE  
WITH A 30 kW  
SOURCE**

**16 MM STAINLESS STEEL** WITH A CUTTING SPEED OF 9 METRES/MINUTE

**20 MM STAINLESS STEEL** WITH A CUTTING SPEED OF 6 METRES/MINUTE

**30 MM STAINLESS STEEL** WITH A CUTTING SPEED OF 600 MM/MINUTE

**50 MM STAINLESS STEEL** WITH A CUTTING SPEED OF 160 MM/MINUTE

**20 MM HARDOX®** WITH A CUTTING SPEED OF 5 METRES/MINUTE

**50 MM CARBON STEEL** WITH A CUTTING SPEED OF 800 MM/MINUTE



**LASER CUTTING SYSTEMS**

# 2D CUTTING SYSTEMS

- **PLUS**

Uncompromising power and accuracy

- **LME**

Accessible laser technology



+ **300**  
systems installed  
in 2021

# PLUS

WORKING AREA UP TO  
**15000x3000 mm**

---

POWER UP TO  
**40 kW**



# PLUS

Cutlite Penta's **FIBER PLUS** family of laser systems combines high **quality**, high **productivity** and low operating costs.

Handling quality is guaranteed by the finest linear motors available on the market which, in conjunction with the Fiber laser source, achieve **the highest levels** of dimensional **accuracy** in cutting both carbon and stainless steels.

These features, together with the simplicity and **stability** of the optical path, converge towards highly optimised, **repeatable** and **dependable** results.

The fluid dynamics of the cutter head, **designed and manufactured** in-house by Cutlite Penta, delivers cuts with lower pressures when compared to the competitors.

This results in a considerable saving in manufacturing costs.

**A few examples:** with a Fiber Plus system equipped with a **30 kW** source, it is possible to cut 16 mm stainless steel at a speed of 9 metres/minute using 5 bar of nitrogen; 20 mm stainless steel at a cutting speed of 6 metres/minute using 6 bar of nitrogen; 30 mm stainless steel at a cutting speed of 2.5 metres/minute using 7 bar of nitrogen.

## Mechanical design

The base is an electro-welded, **thermally stabilised steel** frame, which is then machined to accommodate the high-precision guides and linear motors. The Gantry frame is made up of **cast aluminium alloy tables** to which a steel beam is anchored, which is light and stiff enough to compensate for thermal expansion **with no deformation**. This type of configuration provides remarkable dynamic performance.

## Offcut recovery

The work table is divided into **modular sections** each approximately 500 mm long, which direct the offcuts to the corresponding collection systems located beneath the frame. Each section is equipped with two suction inlets.

## Work table

The work table consists of a **replaceable support grille**. The same laser machine can also be used to produce the grille using a pre-installed program in the numerical control.

## Laser sources

Fiber laser sources provide a great deal of versatility and make it possible to cut a multiplicity of **metal types**. Developed as a single system, it can be paired with a **wide variety of optical fiber diameters**. High efficiency, excellent beam quality and low power consumption are all hallmarks of the source. The source is housed in a **NEMA 12** cabinet which is conditioned and sealed so that it can operate even in the harshest of environments.

The high degree of reliability of these sources ensures very low maintenance costs.

**FIBER PLUS** systems combine high performance levels, structural robustness and increased efficiency. The linear motor drive provides very responsive dynamics, enabling excellent productivity even on extremely complex geometries.

# TECHNICAL SPECIFICATIONS

PLUS MODEL	WORKING AREA
3015	3000x1500mm
3020	3000x2000mm
4020	4000x2000mm
6020	6000x2000mm
6025	6000x2500mm
6030	6000x3000mm
8020	8000x2000mm
8025	8000x2500mm
8030	8000x3000mm
9025	9000x2500mm
9030	9000x3000mm
12030	12000x3000mm
13030	13000x3000mm
14025	14000x2500mm
14030	14000x3000mm
15020	15000x2000mm
15030	15000x3000mm

LASER POWER
2.000 W
3.000 W
4.000 W
6.000 W
8.000 W
12.000 W
15.000 W
20.000 W
30.000 W
40.000 W

**Z-AXIS**

Variable **z-axis** travel as required

**HIGH DYNAMIC PERFORMANCE  
LINEAR MOTORS**

One of CUTLITE PENTA'S strengths is that it can, in certain circumstances, meet customer requirements by **increasing the dimensions** of the system as required.




*Hardox® sample 20 mm*

## STRENGTHS

- In-house designed fiber cutting head.
- Framework with excellent mechanical properties.
- Limited investment and reduced running costs.
- Option of choosing different configurations and adapting the system to suit personal manufacturing requirements.

Our systems correctly reflect the fundamental concepts provided by fiber laser technology, combining efficiency and effectiveness with ease of installation and maintenance, space saving, excellent reliability and high performance. Resulting from the seamless integration of each individual component.



## HARDWARE SOLUTIONS



### **AUTOMATIC NOZZLE REPLACEMENT**

Automatic nozzle replacement is an option whereby the machine automatically changes the cutting head nozzle with no need for operator involvement.



### **CAMERA**

A position camera that enables remote monitoring and viewing of machine operation.



### **TWO-LEVEL WORKTABLE CHANGEOVER**

Two-level worktable changeover allows the table to be changed in approximately 15 seconds, almost completely masking loading and unloading times – the fiber plus system is the fastest on the market today.



### **PALLET LIFT CHANGEOVER**

This optional extra allows optimisation of processing times by reducing loading and unloading times of the sheet metal



### **AUTOMATION**

This option allows optimisation of processing times, almost entirely masking loading and unloading times.



*Iron sample 50 mm*



## FIBER PLUS BEVEL HEAD

**Bevel cutting** is the process of cutting a workpiece with an edge that is not perpendicular to the top of the piece. This is carried out to increase the surface area of the edge for a stronger and more secure weld.

There are a number of different types of bevel edges. Edges are specified throughout the industry by a letter of the alphabet that most closely resembles the shape of the cut as seen in cross-section. The most common types of bevel cut include v, a, x, y upward, y downward and k. The head designed by Cutlite Penta **allows** these processes to be carried out **without compromising** the classic flat cut. The head, which is innovative in its engineering, takes up very little space, it is light and uses the same bases as the flat machines without compromising on any of its technological features. It can also rotate  $\pm 45^\circ$  in both cutting directions.

### STRENGTHS

- Z-axis 350 mm
- Machine dimensions identical to those of a standard plane
- Autofocus cutting head with contact-free capacitive sensor.
- An automatic system for focal length adjustment and 6 sensors for fast piercing
- Sealed lens cartridge
- Protective glass

---

*Iron sample 30 mm*



# LME

WORKING AREA UP TO  
**7000x2000 mm**

---

POWER UP TO  
**15 kW**



The LME laser system family combines the ability to operate at the highest levels of quality with high productivity and low operating costs. The systems are designed to meet the growing demand by small-medium structural metalwork companies for **space-saving machines** but with excellent cutting quality and precision.

LME fulfils this request while maintaining the **linear motor** layout with the **"all in one"** feature of the bigger Plus models, the same cutting head with autofocus and process sensors and the possibility of designing and programming on board the machine in order to make it as versatile as possible.

The fluid dynamics of the cutting head, **designed and produced in-house** by Cutlite Penta, results in high pressure cuts with a lower nitrogen consumption compared to the competition.

This results in a considerable saving in manufacturing costs. All this makes the LME laser system one of the most efficient and reliable on the market.

## Mechanical design

The base is an electro-welded steel frame which is then machined to accommodate the absolute high-precision guides and linear motors.

## Gantry

The gantry frame is made up of a light, sturdy steel beam that is stiff enough to compensate for thermal expansion with no deformation. This type of configuration provides remarkable dynamic performance.

## Offcut recovery

The work surface area is divided into modular sections each approximately

500 mm long, which direct the offcuts to the corresponding collection systems located beneath the frame. Each section is equipped with two suction inlets (these are switched automatically depending on the cutting path).

## Work surface

The work surface consists of a replaceable support grille. The same laser machine can also be used to produce the grille using a pre-installed program in the numerical control. The work grille is adaptable and can be spaced as required for improved processing material handling.

## Laser source

Fiber laser sources of up to 15000 W provide a great deal of versatility and make it possible to cut a multiplicity of metal types. Developed as a single system, it can be paired with a wide variety of optical fiber diameters. High efficiency, excellent beam quality and low power consumption are all hallmarks of the source.

The source is housed in a NEMA 12 cabinet which is conditioned and sealed so that it can operate even in the harshest of environments. The high degree of reliability of these sources also ensures particularly low maintenance costs.

# TECHNICAL SPECIFICATIONS

LME MODEL	WORKING AREA
1010	1000x1000mm
1020	1000x2000mm
1515	1500x1500mm
3015	3000x1500mm
4015	4000x1500mm
4020	4000x2000mm
6020	6000x2000mm
6025	6000x2500mm
7020	7000x2000mm

LASER POWER
2.000 W
3.000 W
4.000 W
6.000 W
8.000 W
12.000 W
15.000 W

Z-AXIS
140 mm

**LINEAR MOTORS**

One of CUTLITE PENTA'S strengths is that it can, in certain circumstances, meet customer requirements by **increasing the dimensions** of the system as required.



*Steel sample 5 mm*

## STRENGTHS

- Small and compact – its footprint on the floor is little larger than its working area.
- Concentrated technology: linear motors, process sensors and autofocus head.
- All in one – electrical panels, laser source, control panel all integrated, which guarantees high speed and excellent accuracy in the cutting process.
- Quick and easy installation, in two days the machine is ready to start manufacturing for the customer.
- CAD/CAM machine integration software

The new LME fiber laser cutting system joins the Cutlite Penta family - it was created to meet the needs of the fashion accessory sector, which has long been calling for small machines with excellent speed and accuracy. This is why the 3015 version makes it an entry-level machine for customers who are currently looking for used machines with outdated technology.



## HARDWARE SOLUTIONS



### **AUTOMATIC NOZZLE REPLACEMENT**

Automatic nozzle replacement is an option whereby the machine automatically changes the cutting head nozzle with no need for operator involvement.



### **CAMERA**

A position camera that enables remote monitoring and viewing of machine operation.



### **TWO-LEVEL WORKTABLE CHANGEOVER**

Two-level worktable changeover allows the table to be changed in approximately 15 seconds, almost completely masking loading and unloading times – the fiber plus system is the fastest on the market today.



### **MANUAL EXTRACTION TABLE**

Manual extraction bench for loading/unloading materials to be processed.



**SOLUTION**

# 2D SOFTWARE SYSTEMS

- **SMART MANAGER 6**
- **SMART COMPOSER**

Our  
**PLUS**  
and **LME**

systems are compatible  
with the main

**CAD/Cam**

available on the market.

# SMART MANAGER 6

## SOFTWARE FOR THE LATEST GENERATION OF **CUTTING SYSTEMS**.

The exclusively in-house designed control software has been evolving in line with market and customer demands for many years. Smart Manager 6 has been specifically developed to fully exploit the potential of the latest generation of cutting systems and guarantee optimum performance of all Cutlite Penta products. The new generation of software includes the many innovations introduced in recent years in laser cutting technology.

The interface improves the already remarkable simplicity and immediacy of operations during daily use, as well as facilitating even the most complex of cutting configurations. The new software is thus now even more intuitive and easier to manage.

In the field of CNCs (computer numerical control) dedicated to laser cutting processes, Smart Manager control provides a variety of improved and revolutionary solutions that aim to simplify and speed up the task of the operator. All this, while ensuring the highest level of safety and quality of work.

A number of the latest innovations implemented with Smart Manager are listed below. Automatic acquisition of plate edges – this feature automatically detects the position of the plate (translation and rotation) and adapts the part-program by automatically translating and rotating it with a typical accuracy of 0.5mm. The plate does not need to be moved on the table..

**Scheduling:** using this tool provided by the control, a list of programmes can be created which are automatically executed in succession depending on their order. This feature allows continuous cycle operation with loading/unloading and sheet metal warehouse..

**Cutting lost:** the system is equipped with light-sensitive sensors which detect cut-losses and thus processing is halted. In addition, program execution can

be restarted automatically just before a cut-loss and at a lower speed than the one programmed.

**Fast piercing:** the system is equipped with photosensitive sensors which optimise the performance and reliability of the sheet metal piercing process, enabling small-diameter perforations to be created in a much shorter time than with traditional piercing systems..

**Smart Focus:** an ultra-rapid autofocus system used to position the focal length during cutting and piercing processes.

**Auto Power Off:** the machine features an automatic power-off system. Synchronous cutting feature: the machine includes a system that optimises release depending on processing distances.

**Raster module (optional):** Cutlite Penta is one of the few companies that supplies a software module for producing high and low relief images with high visual impact. The modular nature of the sources, together with the rapid acceleration of the linear motors, results in realistic three-dimensional images with high throughput.

OUR **PLUS AND LME SYSTEMS**  
ARE COMPATIBLE  
WITH THE MAIN **CAD/CAM SOFTWARE**  
AVAILABLE ON THE MARKET.

# SMART COMPOSER

CUTLITE PENTA'S **REVOLUTIONARY NEW SOFTWARE INTERFACES SEAMLESSLY** WITH THE MACHINE'S NUMERICAL CONTROL AND SMART MANAGER FRONT-END SOFTWARE.

**Geometric elements:** SmartComposer can insert and manage a number of geometric elements and shapes, and allows objects to be moved, rotated, scaled and mirrored. Functions are provided to split, interrupt and lengthen/shorten elements. Edges can be created with a simple click.

**Profile testing:** tools are available for the testing of imported profiles. In particular, invalid, duplicate or open elements can be checked. Node optimisation and reduction.

**RASTER images :** a software module for the creation of high-definition raster images.

**Fiducial markers:** SmartComposer manages markers for plane alignment via camera.

**Management of orders with different materials/thicknesses:** each job can manage a parts order. Parts of different materials and thicknesses can be loaded by changing quantities and descriptions. Automatic multi-level nesting with different materials/thicknesses.

**Micro-joints:** these can be added, either manually or automatically, optionally with lead-ins and lead-outs.

**Lead-in and lead-out management:** these can be added, either manually or automatically. The user chooses the type of lead-in/lead-out on a model workpiece and the software takes care of automatic insertion, observing the position of insertion points.

**Cutting order:** SmartComposer features an effective engine for the calculation of cutting orders. It recognises internal and external tracks and automatically sorts them.

**Cutting order with minimal heating :** SmartComposer can execute a cutting order that minimises heating of the sheet metal.

**Fly cut:** in complete sync with the execution capabilities of the numerical control, fly cutting can be managed, allowing fast execution of tracks containing in-line profiles.

**SmartComposer camera:** smart composer can manage the viewing of the cutting plane by camera. The operator can thus see everything the machine is actually cutting in real time and take a photo of the current plane. This photo, inserted as an image in the background of the cutting table, can be used to manually place workpieces close to an existing offcut.

**Simulator:** SmartComposer is equipped with an nc file simulator and a module for calculating estimates. Acquires nominal speeds directly from the machine for each cutting line and Manages parameters such as cost per kg. Of material and hourly cost.

**Film cutting management:** film cutting is managed depending on material.

**Image film management:** film can be removed from images, either at the workpiece or table level, and the machine can be stopped following removal. Piercing management can be used to set the execution of piercing at both workpiece and table level.

A close-up, low-angle shot of industrial machinery. The scene is dominated by dark, metallic components and several bright blue cables that loop across the frame. The background is blurred, showing more of the factory environment with some yellow safety markings. The overall lighting is dim, creating a professional and technical atmosphere.


**LOAD UNLOADING**

# AUTOMATION

- **LOADING/UNLOADING SYSTEMS**

- **AUTOMATED WAREHOUSES**

**DCS DFS**



# LOADING/UNLOADING SYSTEMS AND WAREHOUSES

AUTOMATION

CUTLITE PENTA ALSO PRODUCES IN-HOUSE IN-LINE OR 90° **LOADING AND UNLOADING** SYSTEMS COMBINED WITH **VERTICAL STORAGE WAREHOUSES** THAT COMMUNICATE DIRECTLY WITH OUR LASER SYSTEMS..

## LOADING/UNLOADING SYSTEM

A suction cup lifting unit mounted on a **carriage that travels** from loading station to laser table, equipped with two electric rear axes driven by absolute transducers.

The lifting unit **moves vertically** for gripping, displacement and sheet metal thickness control. The unit is equipped with **air blast nozzles and wire brushes**.

A fork unloader with ample vertical travel mounted above the outer table of the laser cutting machine.

The forks are driven by two axes controlled by **absolute transducers** which enable them to be lifted and inserted into the laser table beneath the sheet of metal that has been cut. A third motor allows the entire system to be moved "out of the footprint" so that the table area is free and safe from suspended loads in the event of manual loading. On request, the forks can be coated with **anti-scratch material**.

## TECHNICAL DESCRIPTION OF SYSTEM

The metal loading and unloading framework is positioned above the laser pallet changer at **90° or in line** with the pallet changer. It contains a fixed shelf on which the blank material is placed and a motorised shuttle whose homing area is located above the shelf of the material to be cut.

The shuttle picks up the material and takes it to the work table by means of suction cups. The upper part of the shuttle holds a tray for the cut material; during the sheet metal deposit stage onto the work table, the previously

removed cut material is unloaded into the upper tray. At the end of the procedure, the shuttle returns to the homing area.


## DYNAMIC COMPACT STORAGE - DCS

**Highly functional**, vertical storage system with varying numbers of trays. The warehouse framework, which contains the trays, is positioned above the pallet changer, such that the footprint of the framework is masked by the pallet changer. The trays are handled by a highly dynamic shuttle. The framework contains loading units for both metal sheets to be processed and processed ones.

## DYNAMIC FLEXIBLE STORAGE - DFS

The automatic sheet metal loading/unloading system can be connected to an automatic storage warehouse to provide greater autonomy and optimise cutting schedules. The warehouse is designed and constructed according to specific production requirements and in relation to the space available for installation, with the total number of loading units determined according to the height of the area in which it is installed. This system allows both storage of sheets to be processed and the storage of cut material in removable cradles equipped with insertion docks for forklifts. Option of including one or more storage towers.

Both the DCS and DFS systems are controlled by supervisory software that features a simple, intuitive operator interface. This manages the quantities and details of the material in order to ensure the optimal control of available stocks. Both loading and unloading device and automatic warehouse are equipped with all **active and passive safety systems**.



**3015**

Max. sheet metal dimensions	3.025 x 1.520 mm
Max. thickness Single Sheet	25 mm
Max. Weight Single Sheet	900 kg
Indicative loading-unloading time	60/80 s
Sizes (mm)	2000 x 1000 2500 x 1250 3000 x 1500
Loading Tray maximum weight	3600 kg
Loading Tray available height	280 mm
Maximum loadable sheet metal stack height	100 mm
Unloading Tray maximum weight	2700 kg
Unloading Tray available height	280 mm
Maximum unloadable sheet metal stack height	100 mm
Maximum permitted sheet metal deflection	Max 50 mm
Voltage	400 V
Frequency	50 Hz
Power consumption	12 kW (cos $\phi$ = 1)
Maximum current	17.5 A
Pressure	6 bar
Pipe diameter	1/2"

**4020**

Max. sheet metal dimensions	4.025 x 2.025 mm
Max. thickness Single Sheet	25 mm
Max. Weight Single Sheet	1.600 kg
Indicative loading-unloading time	60/80 s
Sizes (mm)	2000 x 1000 2500 x 1250 3000 x 1500 4000 x 1500 4000 x 2000
Loading Tray maximum weight	6400 kg
Loading Tray available height	280 mm
Loadable sheet metal stack height	100 mm
Unloading Tray maximum weight	4800 kg
Unloading Tray available height	280 mm
Unloadable sheet metal stack height	100 mm
Maximum permitted sheet metal deflection	Max 50 mm
Voltage	400 V
Frequency	50 Hz
Power consumption	16 kW (cos $\phi$ = 1)
Maximum current	23 A
Pressure	6 bar
Pipe diameter	1/2"

## 6025

Max. sheet metal dimensions	6.020 x 2.520 mm			
Max. thickness Single Sheet	15 mm			
Max. Weight Single Sheet	1500 kg			
Indicative loading-unloading time	80 s			
Sizes (mm)	2000 x 1000	3000 x 1500	5000 x 2000	8000 x 2000 8000 x 2500
	2000 x 1500	4000 x 1500	6000 x 1500	
	2000 x 2000	4000 x 2000	6000 x 2000	
	2500 x 1250	5000 x 1500	6000 x 2500	
Other sizes	880 x 4000	1000 x 4000	2600 x 1000	2800 x 1000
	880 x 5000	1250 x 4000	2750 x 1250	
Loading Drawer maximum mass	19000 kg			
Loading Tray available height	200 mm			
Unloading Drawer maximum mass	400 kg			
Unloading Tray available height	200 mm			
Maximum permitted sheet metal deflection	50 mm			
Voltage	400 V			
Frequency	50 Hz			
Power consumption	28 kW			
Maximum current	40 A			
Pressure	6 bar			
Pipe diameter	3/4"			
Air consumption / cycle	600 NL			

One of CUTLITE PENTA'S strengths is being able to **meet customer needs by manufacturing each individual component in-house.**

**The dimensions or numbers of load cells** can be modified.



**FIBER LASER**

**LASER SOURCES**



## IPG FIBER LASER

**IPG** was founded in 1991 in Russia by physicist Valentin P. Gapontsev, PhD, a pioneer in the field of fiber lasers.

The company went public in 2006 and is listed on the NASDAQ Global Select Market under the ticker IPGP.

In 1992, the company began to focus on the development of **high-power lasers** and **fiber amplifiers**, and established its global headquarters in the USA in 1998. In 2000, IPG invested in new high-capacity production facilities in the USA to manufacture its own diode pumps, a key component in its fiber lasers and amplifiers.

IPG is highly vertically integrated, producing all the critical components for its lasers and amplifiers. **Fiber optic** technology has had a revolutionary impact on laser manufacturing.

The simplicity and elegance of the fiber laser is reflected in its **efficiency**, compactness, sturdiness and low cost, all of which has led to its tremendous success in the market.



TECHNOLOGY

HARDWARE SOLUTIONS

# HARDWARE SOLUTIONS

ACCESSORY



## **AUTOMATIC NOZZLE REPLACEMENT**

Automatic nozzle replacement is an option whereby the machine automatically changes the cutting head nozzle with no need for operator involvement.



## **CAMERA**

A position camera that enables remote monitoring and viewing of machine operation.


# HARDWARE SOLUTIONS

ACCESSORY



## **PALLET LIFT CHANGEOVER**

This optional extra allows optimisation of processing times by reducing loading and unloading times of the sheet metal.



## **TWO-LEVEL WORKTABLE CHANGEOVER**

Two-level worktable changeover allows the table to be changed in approximately 15 seconds, almost completely masking loading and unloading times – the fiber plus system is the fastest on the market today.



### **AUTOMATION**

This option allows optimisation of processing times, almost entirely masking loading and unloading times.



### **MANUAL EXTRACTION TABLE**

Manual extraction bench for loading/unloading materials to be processed.



*Steel sample 10 mm*





PLUS 20 kW 15000x3000mm



PLUS 30 kW 15000x2000mm



PLUS - DCS



LME - DCS



*Each Cutlite Penta system is not only made of steel and digital circuits.*

*Each system is the brainchild of its designer, who determines the configuration of the machine; it is the vision of the computer scientist who creates intuitive commands and controls; it is the experience of the technician who selects quality materials. Each nut, bolt and bracket embodies the hard work and sweat of those who fashion our machines from bare lumps of metal every day. The ink in the stamp of a sale embodies the sales personnel, who have a profound understanding of customer needs.*

*Each machine is the beating heart of a company, it represents the knowledge of those who dedicate their daily efforts to achieving a goal. Our passion is to be found in each machine.*

*And we want to share this with you.*



Delio Patrizio Mugnaioni  
CEO Cutlite Penta