

HORNET™ G2 200-21



3000
200 BAR
PSI

21
L/PM

HONDA GX390
PETROL
ENGINE TYPE
POWERED by HONDA

GEARBOX
1450RPM
DRIVE

COLD
WATER
OUTPUT



HERO INNOVATIONS



PEXO™
Stainless Steel Exoskeleton



JWPP™
Jetwave Italian Premium Pump



CC™
Centralised Control



AVPS™
Anti Vibration Protection System



MC™
Multi Configuration



LEARN MORE



Registered Design ® 202215870

APPLICATIONS



Tradesmen



Commercial & Exterior Cleaning



Agriculturist



Construction



STANDOUT FEATURES



JW® UDOR® Premium Italian plunger pump running at 1450RPM, delivers more performance and longer life.



Industrial **Honda™ GX390** pull start series engine that delivers performance and reliability.



Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



Heavy duty JW Premium brass adjustable unloader valve. With flat spring design for longevity.



Anti flat all terrain wheels for reliable portability on site.



Emergency stop for increased operator safety.

G2 MORE FEATURES.
MORE INNOVATION.
MORE TECHNOLOGY.

JETWAVEGROUP.COM



STANDARD EQUIPMENT



Gun: (SKU: J5500K) J5500K LTF Spray Gun

Lance: (SKU: JW-007-JB) JW Single Lance with JetBlade nozzle socket

Nozzle: (SKU: JB-2506) 1 x JetBlade nozzle & JetBlade nozzle holder (SKU: JB-NP)

Hose: (SKU: JWA018-SC-ASSY) 10m DWB 3/8" Hose with m22 couplings

Storage: (SKU: G2WASHCASE) G2 Washcase

DIMENSIONS (MM)

TECHNICAL DATA	0:00	HORNET G2 200-21
Product Code	CW3000-21PG2	
Pressure / Flow Rate	3000 PSI (200 BAR) / 21 L/PM (1260 L/PH) / 5.5 GPM	
Max Water Inlet Temp	50°C/ 122°F	
Class (AS/NZS: 4223)	A (4,200 Bar/Litres)	
Usage Frequency	Professional: Daily	
Nozzle Size	06	
Frame Structure	CNC Modular galvanised sheet steel chassis plus satin powder coat finish and stainless steel cover	

MOTOR FEATURES	
Engine / Power	Honda™ GX390 Pull Start (air cooled) 13HP / 390cc
Fuel Type / Capacity / Protection	Unleaded / 6.1L / Low Oil Shutdown

HYDRAULIC FEATURES	
Pump / Head / Pistons	JW® UDOR® Premium Triplex Plunger / Brass (Nickle Plated) / Ceramic
Motor Pump Coupling / Pump RPM	Gearbox Drive / 1450RPM
Unloader Valve	Independent - Adjustable (Panel Mounted)
Safety Valve	Yes

DIMENSIONS & WEIGHT	
Machine Dimensions / Weight	880mm(L) x 575mm(W) x 860mm(H) / 86KG (approx.)

WARRANTY(S)	
Unit / Pump Warranty*	 2 Year(s)
Engine Warranty*	 3 Year(s)

OPTIONAL UPGRADES	SKU	OPTIONAL ACCESSORIES	SKU
JW® PRO RAPID 30M HOSE REEL FITTED WITH 30M HOSE	1060CMPL-HOR30M	JW® PRO TURBO HEAD	JWA303-06
JW® PRO RAPID 60M HOSE REEL FITTED WITH 60M HOSE	1067CMPL-HOR60M	JW® SINGLE BYPASS PRO FOAM COMPLETE KIT	PROFOAM
JW® CONCRETER PACK UPGRADE	PACK-CON	JW® 21" FLAT SURFACE CLEANER - STAINLESS STEEL	JWA-FSC22-5
JW® AGRICULTURE PACK UPGRADE	PACK-AG	JW® TWIN LANCE (WITH PRESSURE CONTROL)	JW54.2

Copyright © 2026 Jetwave® Group Pty Ltd. All Rights Reserved.

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V5.0 01/26

 1800 029 300  sales@jetwave.com.au  jetwavegroup.com